



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁷ :	G06G 7/60, 7/48, 7/58, G06F 17/00, A61B 6/00, A61M 31/00, 29/00	A1	(11) International Publication Number: WO 00/52629
(21) International Application Number:	PCT/US00/05596	(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, LZ, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW, ARPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).	
(22) International Filing Date:	3 March 2000 (03.03.00)		
(30) Priority Data:	60/122,645 3 March 1999 (03.03.99)	US	
(71) Applicant (for all designated States except US):	VIRGINIA COMMONWEALTH UNIVERSITY [US/US]; 1101 E. Marshall Street, Richmond, VA 23298 (US).		
(72) Inventor; and			
(75) Inventor/Applicant (for US only):	STEWART, John, E. [US/US]; 2208 Ashcreek Drive, Richmond, VA 23233 (US).		Published <i>With international search report.</i>
(74) Agents:	MORAN, Michael, J. et al.; Whitham, Curtis & Whitham, 11800 Sunrise Valley Drive, Suite 900, Reston, VA 20191 (US).		

(S4) Title: 3-D SHAPE MEASUREMENTS USING STATISTICAL CURVATURE ANALYSIS

(57) Abstract

A three dimensional curvature algorithm (fig. 1) using linear regression for modeling biological matter. A three dimensional representation of a structure is obtained by scanning the matter. Selected regions of the scanned structure are assigned numerical values. A number of curvature measurements are calculated based on vertices. Linear regression analysis is used to obtain a coefficient of regression for all curvatures. Variance inflation factors are calculated for the curvature measurements. Multiple regressions are performed to obtain a best fit model.

